

# PRODUCT SPECIFICATION SHEET



Rev. C3

## UFO 29H Hermetic Fitting



The UFO 29H downlight fitting allows an airtight seal to be maintained within a display case when using fibre optics.

These fittings are made from aluminium and the air seal is maintained by a series of three o-rings around the flange, eyeball and ferrule. The ferrule is tightened fully onto the fitting and the focus adjustment is made using the trumpet. The further onto the ferrule the trumpet is screwed, the wider the beam. The tight tolerances attained during manufacture help ensure many years of reliable operation.

Supplied with a wide focussing trumpet.

Chrome finish subject to availability, is special order and an extended lead time may be required.

### TECHNICAL INFORMATION

Lens	18mm clear lens
Focus range	25° - 48°
Material	Aluminium
Finishes available	Polished aluminium, black, white, chrome
Weight	19.2g
Mounting hole size	27mm
Ferrule size	M8
Min. fibre size	2mm
Max. fibre size	6mm
Flange size	31.5mm
Articulation	Tilt: 60° / Rotation: 360°

### ORDERING CODES

MODEL	FINISH		TRUMPET		FERRULE SIZE	
UFO 29H	Aluminium	ALU	Wide	W	M8	M8
	Black	BL				
	White	WH				
	Chrome	CH				
UFO 29H						

